



TELL))) SHOCK 2



Your products must be transported carefully? Monitor cost-effectively with Tell-Shock indicators!

Self-adhesive mechanical impact indicator for transport monitoring.


Activation takes place by peeling off the protective film on the reverse side and sticking it with the self-adhesive back to the shipping goods.

Release takes place vertically in the impact angle range between 45 and 90° to the floor.

The window facing the direction of impact turns red when triggered.

Dimension: 48 x 43 x 6 mm Packaging unit: 100 pieces.

- ➔ Guarantee of high safety during the transport of goods.
- ➔ Sensitivity: 5g 10g 15g 25g 37g 50g 75g, at 0.5 to 50 ms impact duration.
- ➔ Lower window red = impact from below / Upper window red = impact from above.
- ➔ Manipulation secured due to serial numbers with barcode.
- ➔ Warning stickers 133x197 mm are included in the delivery.
- ➔ Certified by DEKRA group.



TELL)) SHOCK 2



PRODUKTAUSWAHL PRODUCT SELECTION

kg \ m ³	0.14-0.42	0.42-1.42	1.42-2.83	2.83-7.08	7.08-14.16	14.16-304.8	304.8+
0-5	75G	75G	50G	37G	-	-	-
5-11	75G	50G	50G	37G	25G	-	-
11-23	50G	50G	37G	25G	25G	15G	-
23-45	50G	37G	37G	25G	15G	15G	10G
45-113	37G	37G	25G	25G	15G	15G	10G
113-454	37G	25G	25G	15G	15G	10G	10G
454-907	25G	25G	25G	15G	15G	10G	5G
907-2268	25G	25G	15G	15G	10G	10G	5G
2268-4536	25G	15G	15G	15G	10G	10G	5G
4536-6804	-	15G	15G	10G	10G	5G	5G
6804-9072	-	-	10G	10G	5G	5G	5G
9702-13608	-	-	-	5G	5G	5G	5G
13608+	-	-	-	-	5G	5G	5G

Hinweis: Der Produktauswahl-Leitfaden sollte immer nur als Orientierung verwendet werden.
Note: the selection guide should always be used as starting point only.

Interne Tests sind der beste Weg, um die optimale Auswahl für Ihre Anwendung zu treffen.
Testing is the best way to conduct your application.